

# COOL TOWER 23

## INCUBATORS

This is our benchtop digital incubator tower, featuring two independently controlled 23-liter chambers. With a small footprint, low energy consumption, and user-friendly design, it's the epitome of reliability. This unit is your dependable companion for experiments that demand precise and controlled environments.

### TECHNICAL SPECIFICATIONS


Model	Cool Tower 23 L
Temperature set range	ambient -10°C to 50°C
Controls	digital
Stability	±0,2°C at 37°C
Accuracy	±0,5°C
Capacity	2 x 23 liters
Shelves	3 positions, 2 shelves included(per chamber)
Display	LED
Max. power consumption	80 W / chamber
Chamber Dimension (H x W x D)	270 x 294 x 300 mm
Dimension (H x W x D)	790 x 380 x 470 mm
Crating	545 x 500 x 845 mm
Weight (Net/Crated)	34,0 / 38,5 kg
Permitted working ambient	temperature 2°C to 35°C, rh 75% non-condensing

### ORDER INFORMATION

230 V, 50/60 Hz	Cool Tower 23
Code	220.200
Order ref.	383373
120 V, 50/60 Hz	Cool Tower 23 120 V
Code	1.220.200
Order ref.	383374

### Additional shelf (for 23 liter incubator)

Code	781.1.060
Order ref.	290234
Shelf autoclavable	yes



For more information visit Domel website: <https://labs.domel.com> / Technical specifications subject to change.

Available only outside EU